**PAT-NO:** JP405194919A

**DOCUMENT-IDENTIFIER:** JP 05194919 A

TITLE: RELEASE LINER

PUBN-DATE: August 3, 1993

# **INVENTOR-INFORMATION:**

NAME COUNTRY

JOHNSON, MICHAEL AN/A KUYPERS, MAURICE HN/A

INT-CL (IPC): C09J007/02 , B32B005/08 , B32B027/12

#### ABSTRACT:

PURPOSE: To obtain a release liner in which defects such as breakage and elongation are improved by forming a release layer containing an olefin (co)polymer on the constitutional layer of a reinforcing nonwoven fabric composite containing two layers of specified constitution.

CONSTITUTION: In a reinforcing nonwoven fabric composite having two layers, one layer is composed of fibers (example: nylon fibers) which are substantially arranged randomly, the other layer is a reinforcing nonwoven fabric composite composed of a reinforcing fibers (example: polyester fibers) arranged linearly. A release layer having at least one of an olefin homopolymer (example: polybutylene), an olefin copolymer (example: ethylene-propylene copolymer) and an olefin polar monomer copolymer is formed on at least one layer of the nonwoven fabric composite to produce a release liner. The obtained liner is used appropriately to prevent the fouling of the adhesive layer and other purposes.

COPYRIGHT: (C) 1993, JPO

DERWENT-ACC-NO: 1994-221296

Page 1 of 2

DERWENT-

1994-221296

ACC-NO:

**DERWENT-** 200172

WEEK:

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE:

Release paper for mount for adhesive sheet, tape etc - has release layer formed of mixed resin comprising ethylene

based copolymer and thermoplastic resin

PATENT-ASSIGNEE: DAINIPPON PRINTING CO LTD[NIPQ]

**PRIORITY-DATA:** 1992JP-0332561 (November 18, 1992)

## PATENT-FAMILY:

PUB-NO PUB-DATE LANGUAGE PAGES MAIN-IPC

JP 06155687 A June 3, 1994 006 B32B 027/32B32B 027/32 N/A

JP 3226639 B2 November 5, 2001 N/A 006

#### APPLICATION-DATA:

APPL-DESCRIPTOR APPL-NO PUB-NO APPL-DATE

JP 06155687AN/A

1992JP-0332561 November 18, 1992

JP 3226639B2 N/A

1992JP-0332561 November 18, 1992

JP 3226639B2 Previous Publ. JP 6155687 N/A

INT-CL (IPC): B32B027/00, B32B027/06, B32B027/10, B32B027/32, B32B031/30 , C08L023/08 , C09J007/02 , D21H027/00 ,

D21H027/30

ABSTRACTED-PUB-NO: JP 06155687A

## BASIC-ABSTRACT:

In a sheet of release paper having a release layer in the range of specific surface wetting characteristics: the release layer is formed of a mixed resin comprising (A) an ethylene-based copolymer has density of 0.80 to 0.90 g/cm3, a brittle temp. of -70 deg C or below according to ASTM D746, a Vicat softening temp of 55 to 114 deg C according to ASTM D1525, surface hardness of 42 to 90 according to JIS K6301, and a crystallinity index of 3% or less.

(B) the thermoplastic resin has a density difference above 0.01 g/cm3 compared with the density of (A) ethylene-based copolymer.

USE/ADVANTAGE - Release paper is used as the mount for adhesive

DERWENT-ACC-NO: 1994-221296

sheet, adhesive tape, etc.

Release paper gives stable release without occurrence of paste residue, etc..

CHOSEN-

Dwq.0/0

DRAWING:

TITLE-TERMS: RELEASE PAPER MOUNT ADHESIVE SHEET TAPE RELEASE LAYER

FORMING MIX RESIN COMPRISE ETHYLENE BASED COPOLYMER

THERMOPLASTIC RESIN

DERWENT-CLASS: A17 A81 G03 P73

CPI-CODES: A04-G11; A08-M03; A12-A01; A12-A01A; G02-A05D; G03-B04;

**ENHANCED-** Polymer Index [1.1] 017 ; R00326 G0044 G0033 G0022 D01 D02 **POLYMER-** D12 D10 D51 D53 D58 D82 ; H0011\*R ; A999 A782 ; A999 A351

INDEXING: A340 ; P1150 Polymer Index [1.2] 017 ; B9999 B4831\*R

B4740 ; B9999 B5629 B5572 ; B9999 B3792 B3747 ; B9999 B4773\*R B4740 ; B9999 B4104 B4091 B3838 B3747 ; B9999 B3178 ; K9665 Polymer Index [1.3] 017 ; ND01 ; K9745\*R ; Q9999 Q7205 Q7114 ; B9999 B5390 B5276 ; K9563 K9483 ;

K9483\*R ; K9574 K9483 ; K9676\*R ; B9999 B5334 B5298 B5276
Polymer Index [2.1] 017 ; H0317 ; A999 A782 ; A999 A351
A340 Polymer Index [2.2] 017 ; B9999 B4831\*R B4740 Polymer

Index [2.3] 017 ; ND01 ; K9745\*R ; Q9999 Q7205 Q7114 ;
B9999 B5390 B5276 ; K9563 K9483 ; K9483\*R ; K9574 K9483 ;
K9676\*R ; B9999 B5334 B5298 B5276 Polymer Index [3.1]
017 ; P0000 Polymer Index [3.2] 017 ; Q9999 Q6633 ;

K9676\*R; K9574 K9483; ND01 Polymer Index [3.3] 017;

A999 A351 A340

## POLYMER-MULTIPUNCH-CODES-AND-KEY-SERIALS:

**Key** 0214 0218 0222 0231 0240 2315 2617 2622 2640 2645 2662

**Serials:** 2667 2670 2725 2726 2816 3003 3253 3269

Multipunch 017 034 04- 040 041 046 047 13- 311 314 351 442 443 477

**Codes:** 504 55& 551 556 560 561 575 577 580 59& 597 600 603 604

608 017 04- 040 311 314 442 443 477 55& 575 580 59& 597

600 603 017 04- 314 609 668

## SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1994-100976 Non-CPI Secondary Accession Numbers: N1994-174748